

PU010026

09/805,342

Amendment dated 4/19/2006

**Amendments and Listing of the Claims**

1. (currently amended) An audio reproduction apparatus, comprising:  
a plurality of audio amplifiers, each being responsive to a corresponding audio signal for generating audio power in a corresponding audio speaker; and  
means for selectively applying a supply voltage to a first audio amplifier of said audio amplifiers at a lower magnitude, in a first mode of operation, when audio power generated in a second audio amplifier of said audio amplifiers is higher, and  
at a higher magnitude, in a second mode of operation, when the audio power generated in said second audio amplifier is lower,  
in a manner to provide a constant total audio power output for the system regardless of the number of said speakers ~~reduce a change in a total audio power generated, when a change in the mode of operation occurs.~~
2. (original) The audio reproduction apparatus according to claim 1, further comprising means for selectively enabling audio power generation in said second audio amplifier, in said first mode of operation, and for disabling the audio power generation in said second audio amplifier, in said second mode of operation.
3. (original) The audio reproduction apparatus according to claim 2, wherein the generation of the audio power in said second audio amplifier is enabled in a surround sound mode of operation and disabled in at least one of a monaural mode of operation and a stereo mode of operation.
4. (original) The audio reproduction apparatus according to claim 3, wherein the generation of the audio power in said first audio amplifier is enabled both in said surround sound mode of operation and in said at least one of said monaural and stereo modes of operation.
5. (original) The audio reproduction apparatus according to claim 1, wherein said supply voltage applying means comprises a switch for selectively coupling a source of a first supply voltage to a power supply input of said first audio amplifier, in said

PU010026  
09/805,342  
Amendment dated 4/19/2006

first mode of operation, and a source of a second supply voltage, in said second mode of operation.

6. (original) The audio reproduction apparatus according to claim 1, wherein both said first and second audio amplifiers are energized from a common power supply having a power rating that is determined by the total audio power produced in each of said first and second audio amplifiers.

7. (currently amended) A method for reproducing audio, comprising: providing a plurality of audio amplifiers, each being responsive to a corresponding audio signal for generating audio power in a corresponding audio speaker; and selectively applying a supply voltage to a first audio amplifier of said audio amplifiers at a lower magnitude, in a first mode of operation, when audio power generated in a second audio amplifier of said audio amplifiers is higher, and at a higher magnitude, in a second mode of operation, when the audio power generated in said second audio amplifier is lower, in a manner to provide a constant total audio power output for the system regardless of the number of said speakers ~~reduce a change in a total audio power generated, when a change in the mode of operation occurs.~~

8. (original) The method according to claim 7, further comprising the steps of selectively enabling audio power generation in said second audio amplifier, in said first mode of operation, and disabling the audio power generation in said second audio amplifier, in said second mode of operation.

9. (original) The method according to claim 8, further comprising the steps of enabling the generation of the audio power in said second audio amplifier in a surround sound mode of operation and disabling the generation of the audio power in said second audio amplifier in at least one of a monaural mode of operation and a stereo mode of operation.